

TECHNICAL SPECIFICATIONS – M5

Flow Setting	1 – 5
Electrical Requirements	120V/60Hz 450 watts 5 amps
Oxygen Concentration	92+/-4% @ 1 to 5 Note: higher the flow = higher the purity
Weight	60 lbs
Dimensions	27 in. x 19 in. x 13 in.
Storage Temperature	30 to 160° F
Operating Temperature	55 to 90° F
Operating pressure	8 PSI
Warranty	3 years
Indicators	Power on only

TECHNICAL SPECIFICATIONS – M10

Flow Setting	1 – 5
Electrical Requirements	120V/60Hz 450 watts 5 amps
Oxygen Concentration	92 +/- 4% @ 1 to 5 Note: higher the flow = higher the purity
Weight	60 lbs.
Dimensions	27 in. x 19 in. x 13 in.
Storage temperature	-30 to 160° F
Operating Temperature	55 to 90° F
Operating Pressure	8 to 9 PSI
Warranty	3 years
Indicators	Power on only

TECHNICAL SPECIFICATIONS – M15

Flow Setting	1 – 8
Electrical Requirements	120V/60Hz 600 watts 5 amps
Oxygen Concentration	90+/-5% @ 1 – 8 Note: higher the flow = lower the purity
Weight	60 lbs.
Dimensions	27 in. x 19 in. x 13 in.
Storage temperature	- 30° F to 16° F
Operating Temperature	55° F to 90° F
Operating Pressure	15 PSI
Warranty	3 years
Indicators	power on only

TECHNICAL SPECIFICATIONS – Tornado 2010

Outlet Pressure	18 – 20 PSI
Flow Setting	10 LPM 90% +/- 5%
Electrical Requirements	110V/60 Hz 12 amps
Weight	110 lbs.
Dimensions	15 in. x 17 in. x 23 in.
Storage Temperature	30° F to 160° F
Operating Temperature	55° F to 90° F
Operating Pressure	20 PSI
Warranty	3 years

Note: +/- depends on the ambient temperature, humidity, altitude, etc.

TECHNICAL SPECIFICATIONS – Hurricane 2015

Outlet Pressure	18 - 20 PSI
Flow	15 LPM 90% +/- 5%
Electrical Requirements	110V/60 Hz 12 amps
Weight	110 lbs.
Dimensions	15 in. x 17 in. x 23 in.
Storage Temperature	30° F to 160° F
Operating Temperature	55° F to 90° F
Operating Pressure	20 PSI
Warranty	3 years

Note: +/- depends on the ambient temperature, humidity, altitude, etc.

TECHNICAL SPECIFICATIONS – Psyclone 2020

Outlet Pressure	18 - 20 PSI
Flow	20 LPM 90% +/- 5%
Electrical Requirements	110V/60 Hz 12 amps
Weight	110 lbs.
Dimensions	15 in. x 17 in. x 23 in.
Storage Temperature	30° F to 160° F
Operating Temperature	55° F to 90° F
Operating Pressure	20 PSI
Warranty	3 years

Note: +/- depends on the ambient temperature, humidity, altitude, etc.